

PENNZOIL® FULL SYNTHETIC MOTOR OIL SAE 10W-30

Full Synthetic Motor Oil

TECHNICAL DATA SHEET



PENNZOIL® Full Synthetic motor oil is formulated for modern turbocharged engines. PENNZOIL® utilizes the advances of synthetic technology to provide enhanced wear protection in high and low temperatures and improved cleanliness over synthetic blend motor oils. It meets or exceeds the engine protection required by ILSAC GF-6. PENNZOIL® Full Synthetic offers 40% better performance than Pennzoil® Conventional motor oil.

PERFORMANCE, FEATURES & BENEFITS

- 40% better performance than conventional motor oil.¹
- Fewer oil changes compared to conventional motor oil.
- Enhanced wear protection in high and low temperatures.
- Helps prevent sludge and deposit build up.
- Excellent resistance to oil breakdown in severe environments
- Suitable for use in new and old engines.

1 Compared to Pennzoil® Conventional Motor Oil

MAIN APPLICATIONS

PENNZOIL® Full Synthetic SAE 10W-30 motor oil is recommended for use in all vehicles requiring the use of SAE 10W-30 viscosity grade engine oils under all driving conditions. PENNZOIL® Full Synthetic can be mixed with other synthetic and mineral oils. Always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

TYPICAL PHYSICAL CHARACTERISTICS

Properties	Method	PENNZOIL® Full Synthetic Motor Oil SAE 10W-30
Viscosity Grade	SAE J300	10W-30
Service Category		SP
ILSAC		GF-6A

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

- Chrysler MS 6395
- Ford WSS-M2C947-A

Exceeds the requirements of the following industry specifications:

- API SP -Resource Conserving and all previous Categories
- ILSAC GF-6/A

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk

To find the right Pennzoil product for your vehicles and equipment, please consult www.pennzoil.com to look up the right motor oil recommendation using our oil selector.

© SOPUS Products 2021. All rights reserved.

PENNZOIL® FULL SYNTHETIC MOTOR OIL SAE 10W-30

Full Synthetic Motor Oil

Properties		Method	PENNZOIL® Full Synthetic Motor Oil SAE 10W-30
ACEA			N/A
Density	kg/m ³	ASTM D4052	838.4
Flash Point	°C	ASTM D93	241
Pour Point	°C	ASTM D97	-48
Kinematic Viscosity	@40°C cSt	ASTM D445	64.0
Kinematic Viscosity	@100°C cSt	ASTM D445	10.4
Viscosity Index		ASTM D2270	150
CCS Viscosity	@-30°C cP	ASTM D5293	6 940

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

Advice

Advice on applications not covered here may be obtained from your Shell Lubricants distributor representative or Shell Technical Helpdesk.

To find the right Pennzoil® product for your vehicles and equipment, please consult www.pennzoil.com to look-up the right motor oil recommendation using our oil selector